



NIGHT VISION WEAPON SIGHT **TRIDENT PRO 2 - 2**

The Trident Pro 2 is a rugged night vision weapon sight that provides excellent observation, target acquisition and aiming capabilities for the demanding sports shooter or varmint hunter.

The Trident Pro is available in a variety of Image Intensifier Tube configurations to fit into a wide array of budgets. This scope is designed to withstand the rigors of the environment with a 20m for 1 hour waterproof rating. The best optics, tubes and performance make the Trident Pro scope one of the best night vision weapon sights there is!

- Professional Grade optics
- Illuminated center red reticle for optimal contrast against a dark or light target
- Controls and adjustments are simple and easy to operate
- All external surfaces are a non-reflective matte black finish (except for the optical elements)
- Flip-up back-up iron sights
- Waterproof
- Mounts to standard weaver rails
- The reticle brightness varies from off to full bright with a push of a button
- Trident Pro is designed to use one 3V CR123A type battery
- Afocal 5x magnifier (optional)
- Detachable IR450 infrared illuminator



TRIDENT PRO 2 on the weapon

ACCESSORIES



IR-450
Included



A-focal Doublor (5x)
ACWSTRP2DBLR



Remote control
Included



TRIDENT PRO 2 with A-focal Doublor

SPECIFICATIONS

| | |
|---------------------------------|--------------------------------|
| MAGNIFICATION | 2.5X |
| LENS SYSTEM | F1:1.2, F50 mm |
| FOV | 18° |
| RANGE OF FOCUS | 1m to infinity |
| RETICLE | Red on Green |
| WINDAGE & ELEVATION ADJUSTMENTS | 1/2 MOA |
| IR ILLUMINATOR | Super 450mw |
| POWER SUPPLY | One 3 volt CR123A type battery |
| BATTERY LIFE | 30-50 hours |
| OPERATING TEMPERATURE | -40°C to +50°C |
| STORAGE TEMPERATURE | -50°C to +70°C |
| WATERPROOF | 20 m for 1 hour |
| DIMENSIONS | 250x95x85mm/10"x3.6"x3.2" |
| WEIGHT | 0.9kg/2lbs |

TUBE SPECIFICATIONS

HIGH QUALITY 2+ GEN IMAGE INTENSIFIER TUBE

| | |
|--|----------------|
| DESCRIPTION | Standard |
| GENERATION | 2+ |
| PHOTOCATHODE TYPE | Multi - Alkali |
| RESOLUTION, lp/mm* | 40-45 |
| SIGNAL TO NOISE RATIO* | 12-20 |
| FIGURE OF MERIT | <1250 |
| MTTF - MEAN TIME BEFORE FAILURE, hours | 5,000 |
| EXPORT | N/A for Export |

* Specifications are provided for informational purposes only. Actual values may vary

Export Warning: These products are subject to one or more of the export control laws and regulations of the U.S. Government. Pending the model these products are under the control jurisdiction of either the US Department of State or the US Bureau of Industry and Security US Department of Commerce. Export without proper licensing or consent is strictly prohibited.

1341 San Mateo Ave,
South San Francisco, CA 94080.

www.atncorp.com
e-mail: sales@atncorp.com, info@atncorp.com

Tel: 800-910-2862, 650-989-5100,
fax: 650-875-0129