



P.O. Box 554 Portland, Oregon 97207
503-292-8682 (Phone) 800-722-8078 503-292-8697 (Fax)
info@pr-tech.com www.pr-tech.com sales@pr-tech.com

RECON XT



The Recon XT thermal imager is suited to a range of applications including:

- Law Enforcement
- Security and Surveillance
- Wildland and Structure Fire

Features:

- Cost-effective
- Easy to operate
- Compact
- Rugged
- Worldwide service *
- Day or night full image resolution
- Eliminates need for enhanced light
- Full motion real time video
- Adjustable focus
- Standby mode

New Features:

- 2X-5X Customizable Zoom
- Left or right hand operation
- Optional spot temperature display
- Selectable polarity, white or black hot
- External power and video jacks
- On screen battery level indicator
- Neck strap and ¼-20 tripod mount
- Now with a 2 year warranty



* Subject to export restrictions and licensing

Call 503-292-8682 or visit our website at www.pr-tech.com



Recon XT Specifications

Thermal Imaging Performance

Start-up Time	< 3 seconds
Contrast/Brightness	Automatic/Advanced Image Processing
Range to detect a person	Up to 1500 ft (475 meters) with 25mm Up to 1000 ft (305 meters) with 16mm
Infrared Polarity	Selectable White or Black Hot



with 25mm lens

Focal Plane Array

Detector	Amorphous Silicon Microbolometer
Pixels	160 x 120
Spectral Response	7-14 microns
Thermal Sensitivity	< 50 mK
Refresh Rate	Real-time 30Hz



Optics

Focal Length	8.5 mm	16 mm	25mm
FOV (H x V)	32° x 24°	17° x 12°	11° x 8°
Focus	Manual	Manual	Manual



Video

Output Format	NTSC; Real-Time 30hz Frame Rate PAL; Real-Time 25hz Frame Rate
Output Resolution	NTSC 640x480 pixels for higher clarity PAL 768 x 574 pixels for higher clarity
Viewfinder Display	Monochrome
Viewfinder Dimming	Continuous variable brightness



rear view

Power

Power Source	4 AA batteries
Operating Time	> 6 hours full operation

Environmental Characteristics

Operating Temperature	-4° F to 185°F (-20° C to 85° C)
Storage Temperature	-40° F to 221°F (-40° C to 105° C)
Waterproof	Yes

Model numbers and specifications are subject to change without notice. Subject to export restrictions.



Email us at: info@pr-tech.com

Call us at: 503-292-8682

Fax us at: 503-292-8697

or Toll Free at: 800-722-8078

Visit us at: www.pr-tech.com

